

GOLDEN FAST SEALING

DECORATIVE AND WATERPROOFING CEMENT BASED PAINT

DESCRIPTION

Product in powder which, when mixed with GOLDEN CRYL plus water, creates a protective and decorative coating. In case of application on swimming pools or water reservoirs, mix the product with GOLDEN CRYL (mixture 1 : 2 with water).

ADVANTAGES

- Easy to apply both by brush and by conventional spray equipment.
- It allows a smooth finishing.
- High water vapour permeability.

FIELDS OF USE

- Protection of flower boxes, facades and terraces in concrete.
- Waterproofing finish for swimming pools or water reservoirs.
- Smooth finish over GOLDEN SEAL grey and white.

APPLICATION

The substrate has to be clean, cohesive and sound. Repair damaged areas, cracks or surface faults with a product of the GOLDEN CRETE-line.

Before application, humidify the substrate.

Mix by hand or mechanically with about 32% of mixture GOLDEN CRYL 1:2 in water (for 20 Kg about 6,6 liters of mixture GOLDEN CRYL liquid).

Mix and let the mixture rest for 5 minutes, then remix adding some more mixing liquid up to obtain a creamy consistency.

Apply within an hour from the mixing.

GOLDEN FAST SEALING can be applied by brush, roller or spray; the second shall be applied in case of surfaces with high porosity (within 12 - 24 hours from the first layer application). In case of application in hot, dry and windy conditions, maintain the surface humidified protecting the fresh application by fog-spraying on hardened substrate.

TECHNICAL CHARACTERISTICS (Typical values)

Density:	1.92 ÷ 1.96 Kg/liter
Water vapour permeability μ :	130 ÷ 200
Workability time :	60'
Final setting time :	5 hours

REMARKS

- Do not apply below +5°C.
- Please, contact our Technical Department in case of application in presence with efflorescence, on natural stone or on cellular concrete.

CONSUMPTION

In average conditions, 0.5 kg/m² is sufficient for a thickness of 0.4 mm per layer.

PACKAGING

Product in powder.
Pails of 20 Kg.

COLOURS

Standard colours: white or light grey.
Other colours on request "ad hoc".

STORAGE

Can be kept for 12 months, if stored in protected and dry conditions in the un-opened original packaging at temperature between +5°C and +35°C. Do not keep the product in contact with the ground.

PRECAUTIONS

Like all cement, lime, based products, skin and eyes can be irritated. Wear always gloves and safety glasses. Keep out of reach of children. Do not inhale the powder. In case of contact with eyes or skin, wash abundantly with water, and consult a doctor if irritation persists. In case of doubt, check the Material Safety Datasheet.

The above information may be subject to modifications, which will be announced in the updated technical datasheets. We cannot held responsible for poor results that are due to causes unconnected to the quality if the product.

Date of creation: 01.02.02

GOLDEN FAST SEALING

Date of revision: 02.05.11 Nr. rev.: 4

pag. 2/2

TECNOCHEM ITALIANA S.p.A.

VIA SORTE, 2/4 - 24030 BARZANA (Bergamo) ITALY
TEL. **39 035 55.48.11 - TELEFAX **39 035 55.48.16
E-mail: info@tecnochem.it - www.tecnochem.it