




TECNOCHEM E'
LEED®



From Project to Jobsite



LEED®
Leadership *Engineering*
Environmental *Design*

SILPAINT FIX

WATER BASED FIXATION AGENT AND DILUENT FOR COATINGS BASED ON POTASSIUM SILICATE

Description Binder and solvent for silicate coatings SILPAINT.

Advantages and characteristics Compatible in all proportions with SILPAINT.

Field of application For the dilution of the first layer of SILPAINT, for the preparation of veiling effect treatments with SILPAINT and for the consolidation of existing renders by impregnation.

Precautions

- Do not apply when the temperature is below +5°C.
- Protect and cover any part that does not need to be painted for any spillage during application.
- Avoid spilling on glass, if any spillage, clean immediate with water.

Packaging Cans of 20 Lt.

Technical properties (typical values)	• Aspect:	clear liquid
	• Specific density:	1,03 Kg/lit
	• Application temperature:	from + 5°C to + 35 °C
	• Flammability:	not flammable

Safety indications Read carefully the instructions on the packaging or read the Material Safety Datasheet related to the product before applying.

The above information is based on our best experiences and lab results and on results of the application of the product in various fields. Tecnochem Italiana is not responsible for negative performances due to not proper use of the product or for defects due to elements not connected with the quality of the product included wrong storage. Technical characteristic in this technical data sheet are up-to-dated periodically. Revision date of this technical data sheet is indicated below. Changes of this data sheet can be found in our web-site www.tecnochem.it where you can find the same technical data sheet updated in real time.

Edition: 01/2005
Revision: 09/2012

Nr. rev.: 2

SILPAINT FIX
pag. 1/1