



## SPR 19

### WATERBASED ACRYLIC CONSOLIDATING ADHESIVE

**Description** Transparent, one-component acrylic water dispersion.

- Advantages**
- Easy to inject
  - Transparent.
  - High wetting capabilities.
  - Easy to apply.
  - Dilutions made with water.

**Field of application** Adhesive for injections in between masonry and recuperation adhesive for blisters loosening from plaster, brickwork, etc. Adhesive primer for plasters and brickwork for porous or fragile surfaces.

**Use Preparation of the support**

The surface should be sound, compact, clean and free of oil grease, demoulding oils, etc.

**Application guidelines**

The product is ready to use, but mix product thoroughly before starting the application. The product is to be applied with syringes (as fixing adhesive in masonry) or with a brush or roller (as superficial consolidation). Apply the product until there is a total saturation of the support. If the support is very absorbing a second application can be done at minimum 4 hours after the first. Occasionally the product can be diluted with water.

**Packaging/ colour** Cans of 5 Kg, 10 Kg and 20 Kg.  
Transparent.

**Shelf life** 12 months in the original packaging in a dry and protective area with a temperature between 5°C and 35°C. Protect from freezing.

<b>Technical properties (typical values)</b>	• Specific density	1,06 Kg/l at 20°C
	• Temperature of application	between + 5°C and + 35°C
	• Drying time (touch)	4 hours by 20°C and 65% R.H.
	• Drying time (complete)	12 hours by 20°C and 65% R.H.
	• Dilutions	water

**Safety indications** Read carefully the instructions on the packaging or read the Material Safety Datasheet related to the product before applying.